

2' x 2' Active Ceiling Enclosure for Hubs, Switches, and Patch Panels



A1222-HR



Description:

This plenum-rated Zone Cabling Termination Cabinet mounts in a 2' x 2' ceiling tile grid system. It houses standard 19" rack-mountable hardware with a capacity of up to (2) rack units of active electronics and (5) rack units for any combination of passive connectivity per enclosure. Active devices can be as deep as 15.5" and as tall as 3.5". This assembly includes the doorplate, equipment mounting hardware, and fire-rated foam kits.

Specification:

Height	12"	Width	24"	Length	24"
Weight	39 lbs	Door Weight Capacity	25 lbs	Total Weight Capacity	75 lbs

Door type: Continuous hinge, swing down. Key locks available.

Cable Entry/Exit: (2) 6 inch x 3 inch openings with approved fire-rated foam kits.

Equipment mounting assembly: Mounted on door, compatible with any standard 19" rack-mountable active and passive equipment. Allows for a total of (7) rack units for equipment mounting.

Materials: *Enclosure* - .060 Aluminum *Foam kit* – Polychloroprene latex compound

Packaging: 1 carton / package

Approvals: UL File Number / E185147

Specifications are subject to change without notice.

Revised 8/01

In the U.S. 1-800-285-2070

www.aatk.com

E-mail: service@aatk.com